



PETER LEWIS PAINTS EXTERIOR LIMEWASH

Peter Lewis Paints (PLP) Exterior Limewash, is made from premium quality pigment powders to give our Limewash a natural, chalky soft finish and a wonderful depth of colour. It is made from slaked lime, aged up to 2 years and with a completely breathable finish, our Limewash is particularly suitable for heritage applications.

Location

Exterior.

Suitable Surfaces

The product is for use on suitably prepared surfaces such as plaster, cement render, brick and masonry.

Preparation

Surface must be clean and dry with any friable material, traces of oil and grease removed. Smooth any irregularity of the surface. If surface is sound and in good condition, you can apply PLP Limewash directly onto dampened surface. If surface is unsound, it should be prepared with PLP Lime Silicate Primer to manufacturers specification. If surface is unsound or you are coating over hard set plaster, consult Peter Lewis Paints Technical Department before proceeding.

Application

Product must be well stirred before use. Check the colour before proceeding. PLP Exterior Limewash will dry to a lighter colour than appears in the wet state. Use only stainless steel or plastic stirrers. Two or more coats may be required. Dampen down the surface until the water appears matt and not at all shiny. Work out of direct sunlight. Start at one edge, working a vertical strip, always keeping a wet edge. Apply with a block brush. Allow 24 hours between coats.

Coverage Rates

Approximately 10m² per litre.

Drying Time

All lime-based products have a normal drying time according to the thickness, but the real hardness is obtained through carbonation which occurs on contact with the air. This process could last many months. Protect the surfaces from rain for 24–48 hours after application.

Wash Up

Do not pour leftover paint down drain. Wash all equipment with clean water. Left over paint should be poured or brushed onto paper or newspaper and allowed to dry fully before disposing in general household waste stream.

Note: Never allow waste water to enter storm water drains or sewers.

Recycle

This container is recyclable.

Sizes

Available in 1,4 and 15 Litres.





PETER LEWIS PAINTS EXTERIOR LIMEWASH

(continued)

Safety

Keep out of reach of children. Paint container must be properly sealed at all times when not in use. If contact with the eyes occurs, rinse with running water and seek help if irritation persists. Avoid long periods of skin contact. If swallowed, do not induce vomiting. Give a glass of water and seek medical assistance or contact the Poison Information Centre (13 11 26).

Warranty

Warranty information is available on the Peter Lewis Paints website.

Technical Information

For technical information, please call Peter Lewis Paints on 02 9638 0367.

Manufactured by Peter Lewis Paints. 3–5 Muriel Avenue, Rydalmere, NSW 2116.